

DESCRIPTION

Non-Halogen Cable for 600V Photovoltaic Power System Class 5 TC Stranding Low Smoke Density and Direct Burial Applied.

STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703
ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	10AWG
Stranding	75/0.30mm (0.012inches)
Diameter	2.9mm (0.114inches)
Inner Layer	XLPO
Minimum Average Thickness	0.76mm (0.030inches)
Color	White
Outer Layer	XLPO
Minimum Average Thickness	0.76mm (0.030inches)
Color	Black
Diameter	6.1±0.2mm (0.236±0.008inches)

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
AC	600V
Working Temperature	105°C Dry, 90°C Wet
Insulation Resistance	≥ 1000 MΩ.km (3280GΩ.ft)
Voltage Withstand	4000 VAC
Conductor DC Resistance	≤ 3.61Ω/km (1.10Ω/kft)

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 5 X OD
Static	≥ 4 X OD
Flammability	VW

PRINT LEGEND

BYSON ELECTRONICS 10AWG E331483 (UL) PV WIRE 105°C DRY 90°C WET 600V SUN RES -40°C DIR BUR

HISTORY

Mar 19, 2015	First issue	Draft
Apr 27, 2018	Add "inch" unit	V0