

DESCRIPTIONS

2AWG Tinned Copper Non-Halogen UL 600V

STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703

ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	2AWG
Stranding	266/0.4
Diameter	8.6mm
Primary Insulation	XLPO
Minimum Average Thickness	1.14mm
Color	White (RAL9003)
Secondary Insulation	XLPO
Minimum Average Thickness	1.14mm
Color	Black (RAL9005)
Diameter.	13.5±0.4mm

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
AC	600V
Working Temperature	105°C DRY, 90°C WET
Insulation Resistance	≥ 1000 MΩ.km
Spark test	10000 VAC
Voltage Withstand	4000 VAC
Conductor DC	≤ 0.565 Ω/km

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 5 X O.D.
Static	≥ 4 X O.D.
Flammability	VW-1

PRINT LEGEND

BYSON ELECTRONICS 2AWG E331483 (UL) PV WIRE 105°C DRY 90°C WET 600V SUN RES -40°C DIR

BUR

HISTORY

Apr. 21, 2016 First issue

Draft