

DESCRIPTIONS

6AWG Tinned Copper Non-Halogen UL 1000V, UL 2000V

STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703
ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	6AWG
Stranding	105/0.4
Diameter	5.3mm
Primary Insulation	XLPO
Minimum Average Thickness	1.39mm
Color	White (RAL9003)
Secondary Insulation	XLPO
Minimum Average Thickness	1.14mm
Color	Black (RAL9005)
Diameter.	10.7±0.3mm

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
AC	1000V, 2000V
Working Temperature	105°C Dry, 90°C Wet
Insulation Resistance	≥ 1000 MΩ.km
Spark test	12500 VAC
Voltage Withstand	7500 VAC
Conductor DC	≤ 1.43 Ω/km

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 5 X O.D.
Static	≥ 4 X O.D.
Flammability	VW-1

PRINT LEGEND

BYSON ELECTRONICS 6AWG E331483 (UL) PV WIRE 105°C DRY 90°C WET 2000V SUN RES -40°C DIR
BUR

HISTORY

Apr. 21, 2016 First issue

Draft