

DESCRIPTION

Non-Halogen Cable for 1500V Photovoltaic Power System Class 5 TC Stranding Low Smoke Density and Direct Burial Applied.

STANDARDS

IEC 60228, IEC 60332-1-2, IEC 60754, IEC 60811-2-1, IEC 61034, IEC 61215
 UL 44, UL 854, UL 1581, UL 2556, UL 4703
 EN 50618
 JCS 4517
 Interpretation of EETS Article 46 / H25.03
 ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	10mm ² /8AWG
Stranding	77/0.40
Diameter	4.1mm
Inner Layer	XLPO
Minimum Average Thickness	1.39mm
Color	White (RAL9003)
Outer Layer	XLPO
Minimum Average Thickness	1.2mm
Color	Black (RAL9005)
Diameter	9.4±0.3mm

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	1000V, 2000V
UL 4703	AC: 1000V, DC: Max. 1500V
EN 50618	DC 1500V
JCS 4517	DC 1500V
Interpretation of EETS Article 46	DC 1500V
Insulation Resistance	≥ 1000 MΩ.km
Voltage Withstand	7500 VAC
Conductor DC Resistance	≤ 1.95Ω/km

OTHER CHARACTERISTICS

Dynamic	≥ 5 X OD
Static	≥ 4 X OD
Flammability	IEC 60332-1-2, VW-1, JIS C 3665-1-2
Working Temperature	105°C DRY, 90°C WET

PRINT LEGEND

E331483 (UL) 8AWG PV WIRE 105°C DRY 90°C WET 1000V OR 2000V SUN RES -40°C DIR BUR H1Z2Z2-K 1X10mm² PV
 WIRE BYSON ELECTRONICS S-JET DC 1500V PV-CC 10mm² PV CABLE 90°C

HISTORY

Aug 14, 2015 First issue
 Feb 6, 2017 Changing marking, withdrawn TUV 1990 according to EN standard requirement

Draft
 V0