

## DESCRIPTION

Non-Halogen Cable for 1500V Photovoltaic Power System Class 5 TC Stranding Low Smoke Density and Direct Burial Applied.

## STANDARDS

IEC 60228, IEC 60332-1-2, IEC 60754, IEC 60811-2-1, IEC 61034, IEC 61215  
 UL 44, UL 854, UL 1581, UL 2556, UL 4703  
 EN 50618  
 JCS 4517  
 Interpretation of EETS Article 46 / H25.03  
 ROHS 2011/65/EU

## CABLE CONSTRUCTION



Conductor	Stranded tinned copper
Size	4mm <sup>2</sup> /12AWG
Stranding	52/0.30
Diameter	2.4mm
Inner Layer	XLPO
Minimum Average Thickness	0.76mm
Color	White (RAL9003)
Outer Layer	XLPO
Minimum Average Thickness	1.1mm
Color	Black (RAL9005)
Diameter	6.2±0.2mm

## ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	600V
UL 4703	AC: 1000V, DC: Max. 1500V
EN 50618	DC 1500V
JCS 4517	DC 1500V
Interpretation of EETS Article 46	≥ 1000 MΩ.km
Insulation Resistance	6500 VAC
Voltage Withstand	≤ 5.09Ω/km
Conductor DC Resistance	

## OTHER CHARACTERISTICS

Dynamic	≥ 5 X OD
Static	≥ 4 X OD
Flammability	IEC 60332-1-2, VW-1, JIS C 3665-1-2
Working Temperature	105°C DRY, 90°C WET

## PRINT LEGEND

E331483 (UL) 12AWG PV WIRE 105°C DRY 90°C WET 600V SUN RES -40°C DIR BUR H1Z2Z2-K 1X4mm<sup>2</sup> PV WIRE BYSON  
 ELECTRONICS S-JET DC 1500V PV-CC 4mm<sup>2</sup> PV CABLE 90°C

## HISTORY

Apr 25, 2016	First issue	Draft
Feb 6, 2017	Changing marking, withdrawn TUV 1990 according to EN standard requirement	V0