

DESCRIPTION

Non-Halogen Cable for 600V Photovoltaic Power System Bare Copper Low Smoke Density and Direct Burial Applied.

STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703
ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded Bare Copper
Size	10AWG
Stranding	19/0.595mm (0.023inches)
Diameter	3.0mm ((0.118inches)
Inner Layer	XLPO
Minimum Average Thickness	0.76mm (0.030inches)
Color	White
Outer Layer	XLPO
Minimum Average Thickness	0.76mm (0.030inches)
Color	Black
Diameter	6.2±0.2mm (0.244±0.008inches)

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
AC	600V
Insulation Resistance	≥ 1000 MΩ.km (3280GΩ.ft)
Voltage Withstand	4000 VAC
Conductor DC Resistance	≤ 3.41 Ω/km (1.04Ω/kft)

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 10 X OD
Static	≥ 8 X OD
Flammability	VW
Working Temperature	105°C Dry, 90°C Wet

PRINT LEGEND

BYSON ELECTRONICS 10AWG BC E331483 (UL) PV WIRE 105°C DRY 90°C WET 600V SUN RES -40°C DIR BUR

HISTORY

Feb 4, 2017	First issue	Draft
May 4, 2018	Add "inch" unit	V0