

DESCRIPTION

Non-Halogen Cable for 600V Photovoltaic Power System Bare Copper Low Smoke Density and Direct Burial Applied.

STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703
ROHS 2011/65/EU

CABLE CONSTRUCTION



Conductor	Stranded Bare Copper
Size	4AWG
Stranding	37/0.86mm (0.034inches)
Diameter	6.0mm (0.236inches)
Inner Layer	XLPO
Minimum Average Thickness	1.14mm (0.045inches)
Color	White
Outer Layer	XLPO
Minimum Average Thickness	1.14mm (0.045inches)
Color	Black
Diameter	10.9±0.4mm (0.429±0.016inches)

ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	600V
AC	
Insulation Resistance	≥ 1000 MΩ.km (3280GΩ.ft)
Voltage Withstand	4000 VAC
Conductor DC Resistance	≤ 0.848 Ω/km (0.259Ω/kft)

OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 10 X OD
Static	≥ 15 X OD
Flammability	VW
Working Temperature	105°C Dry, 90°C Wet

PRINT LEGEND

BYSON ELECTRONICS 4AWG BC E331483 (UL) PV WIRE 105°C DRY 90°C WET 600V SUN RES -40°C DIR BUR

HISTORY

Feb 4, 2017 First issue	Draft
May 4, 2018 Add "inch" unit	V0