

## DESCRIPTION

Non-Halogen Cable for 1000V/2000V Photovoltaic Power System Bare Copper Low Smoke Density and Direct Burial Applied.

## STANDARDS

UL 44, UL 854, UL 1581, UL 2556, UL 4703  
ROHS 2011/65/EU

## CABLE CONSTRUCTION



Conductor	Stranded Bare Copper
Size	10AWG
Stranding	19/0.595mm (0.023inches)
Diameter	2.97mm ((0.117inches)
Inner Layer	XLPO
Minimum Average Thickness	1.14mm (0.045inches)
Color	White
Outer Layer	XLPO
Minimum Average Thickness	0.76mm (0.030inches)
Color	Black
Diameter	6.79±0.2mm (0.267±0.008inches)

## ELECTRICAL CHARACTERISTICS (at +20°C)

Voltage Rating	
UL 4703	AC 1000V, 2000V
Working Temperature	105°C Dry, 90°C Wet
Insulation Resistance	≥ 1000 MΩ.km (3280GΩ.ft)
Voltage Withstand	6000 VAC
Conductor DC Resistance	≤ 3.41 Ω/km (1.04Ω/kft)

## OTHER CHARACTERISTICS

Bending Radius	
Dynamic	≥ 10 X OD
Static	≥ 8 X OD
Flammability	VW

## PRINT LEGEND

BYSON ELECTRONICS 10AWG BC E331483 (UL) PV WIRE 105°C DRY 90°C WET 1000V OR 2000V SUN RES -40°C DIR BUR

## HISTORY

Jun 4, 2015	First issue	Draft
Sep 6, 2015	Add "inch" unit	V0
Nov 26, 2015	Marking add "1000V "	V1
Apr 24, 2018	Update file	V2